



High Speed HDMI Cable

ARC, 3D, 4K@30Hz, HDMI Male to Male, Shielded, 1 m (3 ft.), Black

Part No.: [308816](#)

EAN-13: 0766623308816 | UPC: 766623308816

A high-speed cable to deliver high-definition performance.

HDMI has become the standard digital connection, delivering the highest-quality audio and video signal over a single cable. The Manhattan High Speed HDMI Cable is designed and carefully constructed to meet the evolving needs of the high-definition marketplace. This shielded cable provides the highest resolution possible at 4K x 2K, an audio return channel and a bandwidth of 10.2 Gigabits per second at 600 MHz. A high-quality HDMI cable, it provides high-definition video and multi-channel, digital audio with increased performance characteristics, greater accuracy and expanded features.

Features:

- 4K@30Hz Ultra-High-Definition (UHD) resolution supports video resolution up to four times that of 1080p; supports up to 1080p resolution in 3D and Deep Color
- Audio Return Channel (ARC) transmits TV audio through your sound system; no need for additional cable
- Tangle-resistant design allows for easier handling and management; resists cuts and nicks
- Ensures the integrity of the signal between HDMI devices
- Compliant with High Speed HDMI specifications
- Up to 10.2 Gbps at 340 MHz bandwidth
- Fully shielded to reduce EMI and other interference sources
- Compatible with any HDMI device, such as Blu-ray, game consoles, stereos, PCs and more
- Lifetime Warranty

Specifications:

Standards and certifications

- ISO9001

General

- Bandwidth: 10.2 Gbps at 340 MHz
- Meets or exceeds existing HDMI standards
- Length: 1 m (3 ft.)

Connectors

- Two HDMI 19-pin male
- Gold-plated contacts
- Molded PVC boot
- Built-in strain relief

Cable

- 30 AWG cable
- Double shielded
- Current rating: 0.5 A DC
- Withstanding voltage: 300 V DC
- Insulation resistance: 5 MOhms
- Conductive resistance: 1 Ohms
- Thermal plastic casing

Operating Environment

- Operation Temperature: 32 – 104°F (0 – 40°C)
- Storage Temperature: -4 – 140°F (-20 – 60°C)
- Humidity (noncondensing): 0 – 96%

Package Contents:

- High Speed HDMI Cable



